

A brand of  
Aqseptence Group

# Get the Well Pack Sands you need with your Johnson Screens order

Working with local quarries, we now have the ability to offer Well Pack Sands delivered with your Johnson Screens order



US Standard Mesh Size	50# Bags (56 bags = 2800 lbs. pallet) Non-Rescreen	50# Bags (56 bags = 2800 lbs. pallet) Rescreen	3000 lbs. Supersack Non-Rescreen	3000 lbs. Supersack Rescreen
6x9	✓	✓	✓	✓
6x12	N/A	✓	N/A	✓
6x16	N/A	✓	N/A	✓
6x20	N/A	✓	N/A	✓
8x12	N/A	✓	N/A	✓
8x16	✓	✓	✓	✓
8x20	N/A	✓	N/A	✓
10x16	N/A	✓	N/A	✓
12x20	✓	✓	✓	✓
16x30	✓	✓	✓	✓
20x40	✓	✓	✓	✓

# Well Pack Sands Chemical Analyses

Typical Chemical Analyses %	
SiO <sub>2</sub> (Silicon)	99.48
Fe <sub>2</sub> O <sub>3</sub> (Iron Oxide)	0.06
Al <sub>2</sub> O <sub>3</sub> (Aluminum Oxide)	0.21
TiO <sub>2</sub> (Titanium Dioxide)	<0.01
CaO (Calcium Oxide)	<0.01
MgO (Magnesium Oxide)	<0.01



## Requirements on ordering Well Pack Sands

- Minimum Well Pack Sand order is 3 pallets – 3 palletized super sacks or 3 pallets of 56 bags
- Sand freight is not included in freight allowance policy
- There will be situations where we cannot fit all of the sand and the Johnson Screens products on the same truck. Those instances will be evaluated and you will be contacted regarding and additional shipping costs.

## Note

- There is an up charge for rescreened sands
- Rescreened sands receive an additional screening process to remove fines and create a tighter specification product
- Johnson Screens can assist with selection for your application

Typical Physical Analysis	
Mineral	Quartz
ph	Neutral
Color	Tan/White
Roundness	0.6+
Sphericity	0.6+
Hardness	7
Specific Gravity	2.65
Melting Point	2800°-3100° F
LOI Loss of Ignition	0.1
Unit Weight	100 lbs. = 1 cu ft

## Aqseptence Group, Inc. Water Well Screens

North and South America  
 Phone +1 651 636 3900  
 Fax +1 651 638 3177  
[info.johnsonscreens.us@aqseptence.com](mailto:info.johnsonscreens.us@aqseptence.com)

[www.aqseptence.com](http://www.aqseptence.com)