

A brand of Aqseptence Group

Descale Right Nu-Well 100 Pellets



Description

- Dry, pelletized acid that sinks in water for cleaning wells
- Cleans calcium and magnesium carbonate scale, iron deposits and moderate biological growth
- Can be poured directly into the well without dangerous splashing
- Easy to use and handle
- NSF certified for potable water well use

Application

Descale Right pellets are formulated for pouring directly into the well. The pellet form rapidly falls through the water column, providing concentrated acid cleaning power for the screen at the bottom of the well. The sinking pellets are ideal for small diameter wells with screen lengths of 15 ft. or less. Agitation of the acid in the blocked area will greatly enhance cleaning. The acid solution should remain in contact for a period of 12 to 24 hours, depending on the nature of the blockage. The table provides recommended dosages for general well cleaning. The amount of acid consumed will depend on the degree of mineral scaling in the well.

Physical properties, shipping and handling

Appearance: Yellow-brown pellet

Density: Approximately 70 lbs./ft.³

Solubility: Approximately 20% by weight @ 68°F (20°C) (approximately 1 lb./gal. of water)

- Descale Right Pellets are a strong acid-base and should not be stored with strong alkaline materials or oxidizers
- Dust respirators and goggles should be worn where the possibility of dust or mist exists, use in well-ventilated area, wear protective gloves
- Not regulated as a hazardous material under 49CFR 172.101
- Can be shipped by common carrier, DOT Label CORROSIVE
- Additional physical and handling data are available on the product SDS
- Decomposes at 390° F (200°C)
- Available in 4.5, 9, 45, 70, 450 lbs. containers

Standard Dosage Descale Right Recommended Quantities per 5 ft. Screen Length

Screen Diameter (in.)	Number of 1 gal. jars (9 lbs.)
2	1/2
3	1
4	2
5	3
6	4
8	5

Discharge the acid solution from the well, neutralize on the surface and dispose in accordance with the appropriate regulations.

Johnson Screens Water Well Screens

North and South America Phone +1 651 636 3900 info.us@johnsonscreens.com Europe, Middle East & Africa Phone +3 3 23 75 05 42 info.fr@johnsonscreens.com Asia Pacific Phone +61 7 3867 5555 info.au@johnsonscreens.com

johnsonscreens.com

© 2022 Johnson Screens Inc. All rights reserved. Johnson Screens Inc. assumes no liability for possible catalogues, brochures and other printed material errors. The technical data in this brochure is subject to change and for illustrative purposes only and should not be applied as published to your individual case. Johnson Screens reserves the right to alter its products without notice. Any reproduction, distribution, display or use of this information in whole or in part without the written authorization of Johnson Screens is strictly prohibited. 22-WW-0058-v1-4-Eng